



For more information locally

call us direct, or contact:

TB108

Standard UK Specification - Long Dipper/Rubber Tracks

| Engine | | |
|-----------------------|---------------|--|
| Make | Yanmar | |
| Model | RTNV70 | |
| Rated Output (kW)/rpm | 7.1/2400 | |
| Maximum Torque (Nm) | 33 | |
| Cylinders | 2 | |
| Displacement (cc) | 569 | |
| Electrical System | 12volts 34amp | |

| Dimensions and Weight | |
|-------------------------------|-------------|
| Operating Weight inclusive of | 000 |
| bucket and fuel (kg) | 880 |
| Overall Length (mm) | 2740 |
| Width with ROPS (mm) | 740 |
| Width without ROPS (mm) | 680 |
| Height with ROPS (mm) | 2222 |
| Height with Bar Down (mm) | 1415 |
| Ground Clearance (mm) | 160 |
| Min. Front Swing Radius (mm) | 825 |
| Tail Swing Radius (mm) | 740 |
| Dozer Blade (W x H) (mm) | 680-900x200 |

| Operating Information | |
|---------------------------------|------|
| Max Digging Depth (mm) | 1680 |
| Max Dump Height (mm) | 2145 |
| Max Reach at Ground Level (mm) | 2880 |
| Max Vertical Digging Depth (mm) | 1370 |
| Max Bucket Digging Force (kN) | 10.2 |
| Max Arm Digging Force (kN) | 5.8 |
| | |

| Hydraulic System | |
|------------------------|----------|
| Set Pressure (bar) | 160 |
| Pump Type | Gear x 2 |
| Hydraulic Flow (I/min) | 10.7 x 2 |
| Auxiliary Flow (I/min) | 22 |

| Swing System | |
|------------------------|---------|
| Boom Swing Angle (L/R) | 90°/90° |
| Slew Speed (rpm) | 9.3 |
| Slew Motor | Orbital |

| Undercarriage | |
|----------------------------|--------------|
| Traction Motor | Axial Piston |
| Traction Drive | Planetary |
| Traction Brake | Disc |
| Track Width (mm) | 180 |
| Ground Contact Length (mm) | 900 |
| Ground Pressure (kpa) | 25.1 |
| Travel Speed (k/ph) | 2.0/3.9 |
| Maximum Gradeability | 25° |

| Capacities | |
|------------------------|-----|
| Hydraulic System (I) | 14 |
| Fuel Tank (I) | 8 |
| Engine Lubrication (I) | 1.6 |
| Cooling System (I) | 2.5 |

All dimensions unless otherwise stated are in millimetres

In accordance with our established policy of constant improvement, we reserve the right to amend these specifications at any time without notice. tographs shown may feature non-standard equipment.

Takeuchi Mfg (UK) Ltd, Lynroyle Way, Rochdale, Lancashire OL11 3EX Tel: 01706 657 722 Fax: 01706 657 744

Southern Depot at 20 Colthrop Business Park Colthrop Lane, Thatcham, Newbury, Berks RG19 4NB Tel: 01635 877 196 Fax: 01635 877 195

www.takeuchi-mfg.co.uk Email: sales@takeuchi-mfg.co.uk





TB108 Micro Excavator - portable and powerful

The TB108 is our smallest excavator weighing in at just 835kg. Its micro dimensions enable it to pass through a normal doorway making it ideal when working with restricted access. Expands to wider tracks for added stability when digging and tracking.

The TB108 has an impressive dig depth of 1680mm.

EASY ACCESS. EASY SERVICING

Lockable tilt-back steel engine cover secures key parts, components and fuel tank.





EXPANDABLE TRACK FRAME

The TB108 has a unique expanding track frame to adjust from 680mm to 900mm allowing it to travel through narrow openings. Added track width then gives greater operating stability.



WELL PROTECTED HYDRAULICS

One and two-way auxiliary hydraulic circuit, plumbed to the dipper arm, powers a wide range of attachments.



EASY CONTROLS

Easy to drive - simple operating controls make the TB108 an easy to use digger for any level of operator.

TRAILER TOWING -GETS YOU TO THE JOB

The TB108's size and weight make it an easy trailer tow for convenience.

Expanding track frame adjusts from

PERFORMANCE

- 680 to 900mm to travel through narrow openings and greater operating stability.
- Adjustable dozer blade to match expanded track width.
- One and two-way auxiliary hydraulic circuit, plumbed to the dipper arm, powers a wide range of attachments.
- Planetary final drives give better traction on difficult ground.
- Boom mounted work light for all working conditions.

OPERATION

- Two-speed travel provides faster travel over long distances, improving job-site mobility and increasing productivity.
- 180° independent boom swing gives a wider working area.
- Adjustable power and speed for fast cycle times and smooth operation.

SAFETY & SERVICE

- Cast iron wraparound protective counterweight protects the machine and withstands bumps on site -100% steel built for the toughest sites.
- Lockable tilt-back steel engine cover secures key parts and components.
- For servicing the TB108 key features include; fuel and oil hydraulic gauges and an engine oil Safe Drain system.
- Standard safety features include; adjustable seatbelt, safety lockout
 - lever for travel and operating controls.
 - All Takeuchi machines come with 2 year/ 2,000 hours warranty as standard.

OPTIONS

- TKB51 Hydraulic Breaker
- Auger

TB108 Micro Excavator is perfect for landscape, small building and DIY applications.

With an option of six different sized buckets, alternatively add an augur or a breaker and its ready for work.

For difficult ground it has a powerful dig force of 10.2kN.

It gets into places other excavators cannot. It digs deep 1680mm, dumps high 2145mm and has a maximum ground reach as far as 2880mm.

A perfect machine to add to the hire fleet, landscape division or building team.









